



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-GGC

LED Vapor Tight Fixture



The VL-GGC ensures powerful luminosity and provides security for any given location. It is constructed with robust die cast aluminum, built with industrial-grade rubber gaskets and automobile grade aluminum to suit tough weather conditions. This vapor tight fixture is designed to fit in various locations such as: warehouses, docks, restaurants, and any other exterior location. The VL-GGC offers competitive pricing and includes a 5 year warranty.

FEATURES

- Starting Temperature: -40°C
- CRI: 65
- Color temp: 4000K, 5000K
- Driver: Constant current, 120~277V
- Operating life: >50,000 hours
- 5 year warranty

CONSTRUCTION

- Die-cast aluminum body
- Black finish (standard)
- Clear glass lens or frosted glass

OPTIONS

- SF- Single Fuse
- DF- Double Fuse
- SP- Surge Protection

MODEL #	INPUT POWER	LUMEN OUTPUT	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
VL-GGC-14LED	18W	952	4000K	65	>50,000	120~277V	50/60Hz

Ordering Guide

Example: VL-GGC-14LED-40-MV-SB-CLEAR LENS

VL-GGC					
MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
VL-GGC	14W-14LED	40-4000K	MV—120~277V	SB-SAND BLAST	CLEAR LENS FROSTED GLASS

Dimensions

